




Model No. D15027/D15028/D15029/ D15030




Hole size
95-100mm



Hole size
120-125mm



Hole size
165-170mm



Hole size
200-210mm

SPECIFICATIONS:

Installation: Recessed

Housing: Die cast aluminum body

Fixing Bracket: Galvanized steel

Reflector and Diffuser:
Aluminum heat sink and opal diffuser

Driver Multipower: Included. Power factor: >0.95
Maintenance of minimum luminous flux to 80%: 50000

SDCM/L80B10: <3 50,000 hrs


LED type
EPISTAR

Electrical: Meanwell, HEP, Fulham, Tridonic standard driver or optional with dimmable driver

Mounting: Recessed Fixed

Optical flicker: Less than 1% upto 400Hz

Model No.	D15027	D15028	D15029	D15030
Lamps	LED	LED	LED	LED
Wattage	12W	16W	20W	25W
Lumen Output	1320	1760	2200	2750
CRI	≥90	≥90	≥90	≥90
CCT (K)	2700-6500	2700-6500	2700-6500	2700-6500
Power Factor	>0.9	>0.9	>0.9	>0.9
Power	100-240V	100-240V	100-240V	100-240V
Frequency	50/60Hz	50/60Hz	50/60Hz	50/60Hz



Beam angle

